

## OptimaLine4

### **Powerful floodlights for hangar and hall lighting**

The OptimaLine4 convinces with all the advantages of the [OptimaLine2](#) variant but offers even more power in the light output. With 4 COBs, it is the most powerful in its class. With a power consumption of up to 320 W, it has an impressive 46,000 lumens luminous flux.

The OptimaLine4 is also available in two designs: As an FU floodlight with special foiling over the entire inner surface and as a reflector variant with focused light.

It would be our pleasure to advise you on the best solution to fit your specific needs. The compact design, low weight, and low wind load as well as the installation on the existing masts makes the OptimaLine4 popular amongst many customers. The high-power spotlights can also be supplemented by intelligent control and switching devices such as a timer or dimmer function on request. If required, they are also available in bundles of 2 or 3 units.

### **Also available with active cooling**

Depending on the location and desired light output, the OptimaLine can be supplied as an AC version with active power cooling. The active cooling enables more power of up to 540 W at a full 86,000 lm.

Ask our technicians about the best solution for you!

Data Sheets:

[OptimaLine4\\_EN](#)

[OptimaLine4 - Active Performance Cooling\\_EN](#)

[OptimaLine4\\_CL2\\_EN](#)

[OptimaLine4\\_CL2 - Active Performance Cooling\\_EN](#)

[OptimaLine4\\_CL3\\_EN](#)

[OptimaLine4\\_CL3 - Active Performance Cooling\\_EN](#)