

# LED-Pendant Light 4

## Model A-6 HPower LED

The LED pendant lamp 4 is a faithful reconstruction of the A-6 model. Due to its rotationally symmetrical light distribution, this lamp is ideally suited for the illumination of squares, streets, residential areas, green spaces and driveways. The luminaire is equipped with energy-efficient innovative LED technology. Choose between golden-yellow lighting that makes the surroundings appear lively and natural, or very bright safety lighting with convincing light quality.

### Materials:

Luminaire housing: Made of weatherproof natural aluminum  
Hinges and locking parts: Stainless steel or galvanized sheet steel  
Other luminaire components: Galvanized or hot-galvanized steel  
Reflector: Powder-coated to RAL 9016  
Glass dome: Borosilicate glass; design: closed

On request and at an extra charge, paint finishes according to the RAL color table and FerroGrip special coating are available.

### Technical description:

Distribution chamber: 4  
Mounting interface: G1/2 inch external thread  
Accessories: Ball joint G1/2 inch x G1/2 inch



PlugBox: on/off: Switching function on/off

PlugBox ESS Basic: Adjustability of the basic brightness

PlugBox ESS Light: Adjustability of the basic brightness | Adjustability of the reduction brightness

Half-night switching via control voltage 230V AC

MaxiDimm3000: For dimming and/or partial switch-off for balanced and unbalanced Lighting Solutions

Switching input: 230V AC | Interface: 1-10V

Main dimensions:  
Height ca. 632 mm  
Width ca. 382 mm  
Weight ca. 7 kg

### His.lux® LED-Modul Serie 333



#### TECHNICAL DATA

System power ..... 6 - 36 Watt  
Expected Life ..... >60.000 Std.  
Color temperature ..... 2700K\*  
Luminous flux ..... 2225 lm (36 Watt)  
Color rendering ..... CRI > 85  
IP protection class ..... IP 65  
Historical diffuser ..... PC satined  
Application area ..... -40°C bis +55°C  
Protection class ..... I oder II

\*Color temperature freely selectable

### NewNight® Kegel LED-Modul



#### TECHNICAL DATA

System power ..... 8 - 25 Watt  
Expected Life ..... >60.000 Std.  
Color temperature ..... 4100K\*  
Luminous flux ..... 2620 lm  
Color rendering ..... CRI > 85  
IP protection class ..... IP 65  
Historical diffuser ..... PC satined  
Application area ..... -40°C bis +55°C  
Protection class ..... I oder II

\*Color temperature freely selectable

BRAUN Lighting Solutions e. K. is a participant in the export initiative "Energie Effizienz – made in Germany", initiated by the Federal Ministry for the Economy and Technology. Due to the complexity of the many possible combinations of drivers and LED modules, the values shown for technical LED parameters, including performance parameters, are typical. Actual values of specific products in specific configurations may vary from these typical values. The information and diagrams contained in this document do not constitute an offer or contractual obligation. Product parameters may change as a result of technical innovation and will be undertaken without prior notice. Our manufacturing conforms to DIN EN and VDE regulations; the product conforms to European EMC regulations.