

His.lux[®] LED universal module 4

BRAUN[®] LED module L7 (IoT-Ready)

Technical Description

His.lux universal module 4, which is based on the special aesthetics of gas lighting. Suitable for use in decorative luminaires of all kinds. Use the symmetrical light distribution to customise your lighting project.



| BRAUN [®] His.lux L7 | |
|-----------------------------------|---|
| Module series | L7 |
| Power | 38,2 Watts (0,7A) 29,7 Watts (0,53A) 20,2 Watts (0,35A) |
| LED luminous flux ¹ | 3357 lm 2588 lm 1780 lm |
| Light colour | warmwhite |
| Colour temperatures | 1800 K 2000 K 2200 K 2700 K 3000 K |
| Colour rendering index (CRI) | 70 (optional: 80 or 90) |
| Degree of protection LED room | IP66 |
| light distribution | symmetrical |
| Power control | DALI-2 D4i |
| Permissible operating voltage | 230V AC / 50Hz |
| Permissible operating temperature | -40°C to 55°C |
| LED control gear | IP66/67 ENEC CE |
| Overtoltage protection | up to 6 kV |
| Protection class | I or II |

¹Rated luminous flux at 2700 K (CRI 90)

BRAUN Lighting Solutions e. K. is part of the export initiative 'Energy Efficiency - made in Germany' - initiated by the Federal Ministry of Economics and Technology. Due to the complex combination possibilities of different power supply units and LED modules, the typical values given for the technical LED parameters and the performance parameters are purely statistical values that do not necessarily correspond to the actual technical parameters of each individual product, which may deviate from the typical value. The information and illustrations contained in this document are not part of an offer or contract. Product parameters may change due to technical innovations and are subject to change without prior notice. Manufactured in accordance with DIN EN, VDE regulations, CE.

BRAUN Lighting Solutions e.K.
Nunsdorfer Ring 2-10
12277 Berlin
Germany

www.braun.lighting
info@braun-lighting.com
+49 (0)30 7 007 763 100
+49 (0)30 7 007 763 101

